

Standard filters

MODEL

F0010

Filter capacity	l/min	1167	Flow rates at 7 bar and 20°C
	m ³ /h	70	
Working pressure	bar	7 (16 max)	
Air connections	IN/OUT	½" BSP	
Net weight	Kg	0,6	
Standard type of drain	Manual		

QF - Dust Filtration
 PF - General purpose Protection Filtration
 HF - High Efficiency Oil Removal Filtration
 CF - Activated Carbon Filtration

Filtration grade		QF	PF	HF	CF
Complete filter code		04A.0060.QG00	04A.0060.PG00	04A.0060.HG00	04A.0060.CG00
Filter element code		04E.0060.Q	04E.0060.P	04E.0060.H	04E.0060.C
Physical filtration process		Interception	Interception + coalescing	Interception + coalescing	Adsorption
Max solid dimension intercepted (ISO 8573-1)	µm	1 µ	0,1 µ	0,01 µ	//
Max solid dimension intercepted (ISO 8573-1)	Class	3	2	1	//
Remaining oil content after filtration (ISO 8573-1)	mg/m ³	//	0,1 mg/m ³	0,01 mg/m ³	0,003 mg/m ³
Remaining oil content after filtration (ISO 8573-1)	Class	//	2	1	//
Max temperature	°C	100	100	100	60
Pressure drop with new element	bar	0,05	0,1	0,1	0,08
Pressure drop with saturated elements	bar	0,6	0,6	0,6	0,6
Element replacement time	hours	4000 h	3500 h	3500 h	3000 h
Element replacement time	months	6	5	5	4

Line pressure [bar]	1	2	3	5	7	9	11	13	15	16
Correction factor	0,20	0,36	0,50	0,75	1,00	1,25	1,50	1,75	2,00	2,13

Dimensions (mm)	
A	220
B	90
C	25
D	80

